

MOBILE CONE CRUSHER

USE THE **300c-t** TO
MAXIMIZE YOUR CAPACITY

This heavy duty 300c-t tracked cone crusher features an innovative material flow that maximizes capacity and throughput while delivering a consistently high-quality product. The tracks enhance the job site mobility of this crusher, ideal for any spread.

- 510Hp D13 Volvo Penta engine/
516Hp C13 CAT LRC /
536Hp C13 CAT Stage V
- Integrated hopper with folding
rear door
- I-beam plate fabricated chassis
construction
- Large gap between crusher
discharge and main conveyor
feedboot
- Open chassis design for ease
of maintenance
- Fast setup time
- Tracked

LIPPMANN

300c-t TECHNICAL SPECIFICATIONS

CRUSHING CHAMBER	
Feed Opening	41" (1050mm)
Crusher Drive	Direct Drive
Min. Opening	0.5" 4.21" (13mm 107mm)
Max. Opening	0.75" 8.31" (19mm 211mm)
CSS Adjustment	Hydraulic
Level Sensor	Ultrasonic
Throw	84mm

HOPPER	
Hopper Length	12' 4.9" (3780mm)
Hopper Width	7' 2" (2200mm)
Hopper Volume	6.5 yd ³ (5m ³)

FEEDER	
Feeder Operating Width	36" (910mm)
Feeder Belt Width	48" (1200mm)
Adjustable Speed	YES
Drive	Hydraulic

CONVEYOR	
Stockpile Height	12' 9" (3887mm)
Belt Width	48" (1200mm)
Angle Adjustable	YES
Quick Release	YES

ENGINE	
Engine	VOLVO D13 Tier 5 or Tier 3
Engine Power	510 hp (380kW)
Fuel Tank Capacity	290 US gal (1100L)
Hydraulic Tank Capacity	211 US gal (800L)

DIMENSIONS	
Transport Length	57' 4" (17.5m)
Transport Width	10' 4" (3.15m)
Transport Height	11' 9.7" (3.6m)
Operation Length	51' 3" (15.62m)

TOTAL WEIGHT	
Total Weight	108,026 lbs (EST.) 49,000kg (EST.)

LIPPMANN

3271 East Van Norman Avenue
Cudahy, WI 53110

Lippmann-Milwaukee.com

800-648-0486

AUTHORIZED DISTRIBUTOR