

## PORTABLE CONE CRUSHER

THE **300c-wrd** EXCEEDS  
YOUR PRODUCTIVITY NEEDS

With high productivity of the 44" cone on the 300c-wrd, this wheeled rear discharge plant exceeds your productivity needs in your crushing spread. Featuring fully guarded moving components and controls that are located a safe distance from the moving components, this 300c plant puts safety first.

- Lockable - 8hp electric start  
Honda powered hydraulic  
power pack
- Full length wheel fenders
- 4x hydraulic jack legs
- 6x drop down crib legs
- 2x hydraulic front support legs
- Overflow chute & storage  
for transport

**LIPPMANN**

# 300c-wrd TECHNICAL SPECIFICATIONS

CRUSHING CHAMBER	
Feed Opening	8.31" (211mm)
Crusher Drive	2x Banded V-Belts
Min. Opening	0.50" (13mm)
Max. Opening	0.75" (19mm)
CSS Adjustment	Hydraulic
Level Sensor	Optional

POWER	
Panel	Wired to terminal box w. opt NEMA-12 motor control center
Voltage	460V   575V
Hydraulic Tank Capacity	20 US gal (76L)

CONVEYOR	
Stockpile Height	165" (4191mm)
Width	42" (1067mm)
Length	40' 6" (12.33m)
Angle Adjustable	YES

DIMENSIONS	
Transport Length	58' 5" (17.81m)
Transport Width	11' 5" (3.48m)
Transport Height	13' 7" (4.14m)
Operation Length	64' 1" (19.53m)

TOTAL WEIGHT	
Total Weight	98,000 lbs (44,452kg (EST.))

# LIPPMANN

3271 East Van Norman Avenue  
Cudahy, WI 53110

[Lippmann-Milwaukee.com](http://Lippmann-Milwaukee.com)

800-648-0486

AUTHORIZED DISTRIBUTOR