

MOBILE CONE CRUSHER

DEPEND ON THE **400c-t** FOR
MOBILITY AND TOUGHNESS

When mobility and toughness matter in the most abrasive environments, count on Lippmann's 400c. This heavy-duty cone crusher lets you feed directly into the plant to handle larger, secondary rock it might see from a big, primary crusher.

- 612Hp D16 Volvo Penta engine
- Large gap between crusher discharge and main conveyor feedboot
- Integrated hopper with folding rear door
- I-beam plate fabricated chassis construction
- Tracked
- Open chassis design for ease of maintenance
- Fast setup time

LIPPMANN

400c-t TECHNICAL SPECIFICATIONS

PAN FEEDER	
Feed Opening	44.5" (1130mm)
Crusher Drive	Direct Drive
Min. Opening	0.79" 7.8" (20mm 198mm)
Max. Opening	1.18" 11.77" (30mm 299mm)
CSS Adjustment	Hydraulic
Level Sensor	Ultrasonic
Throw	95mm

HOPPER	
Hopper Length	12' 4.9" (3780mm)
Hopper Width	7' 2" (2200mm)
Hopper Volume	6.5 yd ³ (5m ³)

FEEDER	
Feeder Opening Width	36" (910mm)
Feeder Belt Width	48" (1200mm)
Adjustable Speed	YES
Drive	Hydraulic

CONVEYOR	
Stockpile Height	10' 3" (3124mm)
Belt Width	48" (1200mm)
Angle Adjustable	YES
Quick Release	YES

ENGINE	
Engine	VOLVO D16 Tier 4 or Tier 3
Engine Power	612 hp (456kW)
Fuel Tank Capacity	290 US gal (1100L)
Hydraulic Tank Capacity	211 US gal (800L)

DIMENSIONS	
Transport Length	55' 0" (16.76m)
Transport Width	12' 0" (3.66m)
Transport Height	11' 9.7" (3.6m)
Operation Length	51' 2.6" (15.61m)

TOTAL WEIGHT	
Total Weight	123,459 lbs (EST.) 56,000kg (EST.)

LIPPMANN

3271 East Van Norman Avenue
Cudahy, WI 53110

Lippmann-Milwaukee.com

800-648-0486

AUTHORIZED DISTRIBUTOR